



# Industrial sweeper

SI



## Technical Specification



**Sweeper** with polypropylene bristles to clean and collect dust on all surfaces, both in and outdoor.

Frame with **360° pivoting front wheels**.







**Collection bucket** with tilt hydraulic cylinder.

Easy matching with machines like skid loaders, articulated wheel loaders, fork lifts, telescopic handlers, etc.

**Fully hydraulic**, including collection bucket opening. **Excellent sweeping** thanks to the **floating linkage** copying the ground.

Sprinkler with water tank, 12V electric pump and nozzles to pulverize water (on request).

# Industrial sweeper

MODEL		SI 1200	SI 1500	SI 1800	SI 2100	SI 2200	SI 2400	
<b>Technical specification</b>	um							
Working width	mm	1200	1500	1800	2100	2200	2400	
Overall width	mm	1345	1645	1945	2245	2405	2605	
Oil flow, min-max	lt/min	25-50	25-60	40-80		70-120	100-120	
Oil pressure, min-max	bar	120-200		160-200		200-240		
Weight standard configuration	kg	350	400	460	490	740	800	
Best broom speed	rpm	120						
Broom ring	Ø mm	580 x n. 38	580 x n. 49	580 x n. 59	580 x n. 69	650 x n. 73	650 x n. 79	
Water tank capacity <sup>(1)</sup>	lt	100						
Collection bucket capacity	lt	230	290	350	410	530	580	
 ton		2,0-2,6	2,4-3,5	3,0-4,0	3,8-5,0	–	–	
 ton		2,0-3,0	2,0-4,0	3,5-5,0	4,5-7,0	–	–	
 ton		2,2-3,5	3,2-4,5	4,0-5,5	4,6-6,8	5,8-8,5	7,5-12,0	
 ton		2,4-3,8	3,4-5,0	4,5-6,0	5,6-7,5	7,0-9,0	8,0-10,0	
 ton		–	–	4,0-5,0	4,5-6,0	5,8-8,5	7,5-12,0	
	Overall size in standard configuration	A cm	135	165	195	225	240	260
		B cm	81	81	81	81	89	89
		C cm	154	154	154	154	182	182

<sup>(1)</sup> Optional

Collection bucket with tilt hydraulic cylinder



## ACCESSORIES FOR OPERATING MACHINES



Via E. Mattei, 4 - 48012 Bagnacavallo RA - Italy  
tel +39 0545 62712 fax +39 0545 62140  
info@gfgordini.com - www.gfgordini.com

YOUR BEST CHOICE SINCE 1985.

