



Mini mulcher and mulcher



Mini Mulcher

MTC



Mulcher

TC







Technical Specification

Mulcher to top grass and grind shrubs with diameter up to 5-6 cm.
Adjustable **rear roller** to set cutting height.
Floating hitch for best roller contact with ground.
Side skids with replaceable runners.

Forged and tempered hammers.
Hoses for connection to machine with **3 hydraulic lines**.
Hitch with **sideshift device**: 40 cm to the right for road verge work (for TC models).



Mini mulcher and mulcher

		Standard flow				High flow			
MODEL		MTC 115	MTC 125	MTC 145	TC 145	TC 160	TC 180	TC 200	
Technical specification	um								
Working width	mm	1150	1250	1450	1450	1600	1800	2000	
Oil flow, min-max	lt/min	30-40			50-70	70-90		90-110	
Oil pressure, min-max	bar	180-200				180-220			
Weight standard configuration	kg	220	235	250	640	690	720	780	
Right mechanical sideshift ⁽¹⁾		-			400				
Max cutting	Ø mm	25	25	25	50	50	60		
Hammer	n.	32	34	40	14	14	16	18	
	ton	1,7-2,5	2,0-2,8	2,5-3,6	2,2-2,8	2,6-3,8	3,4-4,4	4,0-4,8	
	ton	2,2-3,0	2,5-3,5	3,0-4,4	3,0-4,8	4,6-5,6	5,0-6,2	6,0-8,0	
	ton	-	-	-	-	-	5,2-7,0	6,8-9,0	
	Overall size in standard configuration	A cm	169	184	204	169	184	204	224
		B cm	93	93	93	93	93	93	93
		C cm	135	135	135	135	135	135	135

⁽¹⁾ On request



Data, descriptions and images of this document are not binding hence GF Gordini reserves the right to alter part or all of them at any time with no notice.

ACCESSORIES FOR OPERATING MACHINES



Via E. Mattei, 4 - 48012 Bagnacavallo RA - Italy
tel + 39 0545 62712 fax +39 0545 62140
info@gfgordini.com - www.gfgordini.com

YOUR BEST CHOICE SINCE 1985.

